Xerox® Phaser® 6600
Colour Printer and
Xerox® WorkCentre® 6605
Colour Multifunction Printer

	Phaser 6600N	Phaser 6600DN	WorkCentre 6605N	WorkCentre 6605DN
Output Speed – Colour and Black and White				
One-sided	Up to 36 ppm 8.5 x 11 in. Up to 35 ppm A4 (210 x 297 mm)			
Automatic Two-sided	N/A	Up to 24 ppm 8.5 x 11 in. Up to 24 ppm A4 (210 x 297 mm)	N/A	Up to 24 ppm 8.5 x 11 in. Up to 24 ppm A4 (210 x 297 mm)
Paper Handling – Input				
Duplex Automatic Document Feeder (DADF)				
Capacity¹	N/A		50 sheets	
Sizes			Custom Sizes: 5 x 5 in. to 8.5 x 14 in. / 140 x 140 mm to 216 x 356 mm	
Weights			Simplex: 13 lb. to 32 lb. bond / 50 to 125 gsm Duplex: 16 lb. bond to 32 lb. cover / 60 to 125 gsm	
Multipurpose Tray				
Capacity¹	150 sheets			
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76.2 x 127 mm to 216 x 356 mm			
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm			
Media Types	Plain paper Hole punched Letterhead Coloured Lightweight Card Stock Lightweight Glossy Card Stock Heavyweight Card Stock Heavyweigt Glossy Card Stock Labels Envelopes			
Tray 1				
Capacity¹	550 sheets			
Sizes	Sizes: 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm			
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm			
Media Types	Plain paper Hole punched Letterhead Coloured Lightweight Card Stock Lightweight Glossy Card Stock Heavyweight Card Stock Heavyweigt Glossy Card Stock			

Xerox® Phaser® 6600 and Xerox® WorkCentre® 6605

Tray 2 (Optional)	
Capacity[1]	550 sheets
Sizes	Sizes: 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm
Media Types	Plain paper Hole punched Letterhead Coloured Lightweight Card Stock Lightweight Glossy Card Stock Heavyweight Card Stock Heavyweigt Glossy Card Stock

Paper Input Capacity			
Standard Capacity[1]	700 sheets		
Maximum Capacity[1]	1250 sheets		

Paper Output	Phaser 6600N	Phaser 6600DN	WorkCentre 6605N	WorkCentre 6605DN
Output Capacity[1]	250 sheets			
Automatic Two-sided Output	N/A	Standard	N/A	Standard

Print		
First-page-out Time	As fast as 9 seconds black and white / 10 seconds colour	
Print Resolution	Up to 600 x 600 x 4 dpi (1200 x 1200 enhanced image quality)	
Maximum Print Area	4.1 mm from all edges	
Memory (Std/max)	256 MB / 768 MB	512 MB / 1 GB
Optional Hard Drive	160 GB	
Processor	533 MHz	
Language Support	True Adobe® Postscript® 3™ PCL® 5 PCL® 6 XPS PDF Emulation	
Connectivity	USB 2.0 10/100/1000Base-TX Ethernet Optional Wi-Fi (802.11 n/g/b)	
Printing Features	PANTONE® Colour calibrated solid-colour simulations Saved settings Earth Smart settings Colour Corrections N-up Booklet layout Watermark Photo mode Collation Secure Print (Standard on WorkCentre 6605, requires optional Productivity Kit on Phaser 6600) Saved Print (Standard on WorkCentre 6605, requires optional Productivity Kit on Phaser 6600) Font/Form/Macro Storage (Requires Productivity Kit (with 160 GB Hard Drive)) Apple AirPrint™	

Supported Operating Systems	Microsoft® Windows® XP SP1, Vista, 7, 2008 Server, 2003 Server
	Mac OS® 10.5 and later
	Various Linux and Unix distributions, including:
	   IBM® AIX® 5
	   HP-UX® 11i v2
	   Open SUSE® 11
	   Red Hat® Fedora® Core 11-14
	   Ubuntu®	

Print Drivers	Windows® XP and later Mac OS® 10.5 and later Xerox® Global Print Driver® Xerox® Mobile Express Driver®	
Font Capability	176 PostScript® fonts 88 PCL® fonts	

Xerox® Phaser® 6600 and Xerox® WorkCentre® 6605

Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Xerox® Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. • Printers are automatically discovered • Printer list can be managed based on location • Gives Bidirectional feedback device status, supplies, queue management
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. • Printers are automatically discovered • Printer list can be managed based on location • Gives Bidirectional feedback device status, supplies, queue management

Copy	Phaser 6600	WorkCentre 6605
Copy Speed		Simplex: Up to 36 ipm (images per minute) 8.5 x 11 in. / 35 ipm A4 Duplex: Up to 24 ipm 8.5 x 11 in. / A4
Document Scanner		Duplex Automatic Document Feeder with 50-sheet capacity
Document Scanner Size		Platen: Up to 8.5 x 11 in. / A4 DADF: Up to 8.5 x 14 in. / 216 x 356 mm
Sides (input:output)		1:1, 1:2, 2:2 and 2:1
Quantity		1 to 99
Resolution		Up to 600 x 600 dpi
First-copy-out Time		As fast as 13 seconds black and white / 16 seconds colour
Copy Features		Reduce/Enlarge (25%–400%) Lighter/Darker Colour Saturation Sharpness Colour Balance Auto Exposure 2-up Output AutoFit Cloning Collate (up to 50 pages)

Fax	Phaser 6600	WorkCentre 6605
Fax Speed		33.6 Kbps
Memory		4 MB
Resolution		Up to 300 x 300 dpi (Super Fine / Photo) resolution Up to 203 x 196 dpi (Fine) resolution Up to 203 x 98 dpi (Standard) resolution
Compression		MH, MR, MMR, JBIG
Walk-up Fax Features (analogue phone line required)		Reject Junk Fax Distinctive Ring Pattern Detection Fax Forward to Email and FTP/SMB Server[4] Fax Forwarding and Local Print Polling Receive Delayed Start (up too 24 hours) Broadcast Sending (up to 200 destinations) Fax Address Book (up to 200 speed dials) Secure Fax Receive
LAN Fax Features		Delayed Start (up to 24 hours) Broadcast Sending (up to 30 destinations) Zoom Auto Fit Rotation N-up Watermark Phonebook (Up to 500 speed dial numbers, up to 500 group dials, phonebook stored on PC)

Xerox® Phaser® 6600 and Xerox® WorkCentre® 6605

Scan	Phaser 6600	WorkCentre 6605
Capability	N/A	Black and white and colour scanning
Input Speed – B/W		Simplex: Scan up to 22 ipm – 8.5 x 11 in. / A4 Duplex: Scan up to 7 ipm – 8.5 x 11 in. / A4
Input Speed – Colour		Simplex: Scan up to 13 ipm – 8.5 x 11 in. / A4 Scan up to 4 ipm – 8.5 x 11 in. / A4
Resolution (maximum)		Up to 1200 x 1200 dpi
Bit Depth		48-bit colour, 16-bit greyscale
Maximum Scan Area		Platen: Up to 8.5 x 11 in. / A4 DADF: Up to 8.5 x 14 in. / 216 x 356 mm
Network Filing Protocol		FTP SMB
File Formats		PDF TIFF (single and multi-page) JPEG
Scan Driver Compatibility		WIA TWAIN
Supported Scan Destinations		Scan to Computer via SMB Scan to Server via FTP Scan to Email with LDAP support Scan to USB Memory Device WSD Scanning

Scanning Solutions		
Xerox® Scan to PC Desktop Personal Edition	N/A	A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools • Nuance PaperPort – image viewing and file management software • Nuance OmniPage (for desktop/client installation) – OCR and file format conversion software • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops.
		For more information, visit **www.xerox.com/scan2pcSE**.

Security		
Security Features	Secure Fax Receive (WorkCentre 6605 only) Secure Print (Standard on WorkCentre 6605, requires optional Productivity Kit on Phaser 6600) 256-bit disk encryption and overwrite (Requires Productivity Kit (with 160 GB Hard Drive)) Secure HTTPS (SSL, Secure LDAP (Requires Productivity Kit (with 160 GB Hard Drive))) IPsec 802.1X Authentication IPv6 SNMPv3 Audit Log IP Filtering Scan to Email over SSL/TLS	

Wi-Fi Security			
	Authentication Method	**Encryption**	**Hard Drive Required**
	Open WPA PSK WPA PSK / WPA2 PSK	WEP 64/128 ASCII/HEX TKIP AES	No
	WPA Enterprise WPA Enterprise / WPA 2 Enterprise WPA Enterprise AuthenticationMethod options: PEAPVO MS-CHAPV2 EAP-TLS EAP-TTLS PAP EAP-TTLS CHAP	TKIP AES	Yes

Xerox® Phaser® 6600 and Xerox® WorkCentre® 6605

Device Management

Xerox® CentreWare® Web

	• A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management

Xerox® CentreWare Internet Services – Integrated Device Web Page

Device Status	Web server embedded • Tray status/contents • Consumables status
Print Queue Viewing	Complete job print queue management – hold, release, promote and delete
Job Submission	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Microsoft® Internet Explorer 7 Firefox® version 4 and above

Xerox® Mobile Solutions

Xerox® Mobile Express Driver®	The Xerox® Mobile Express Driver is a single, universal printer driver that can be downloaded to a PC and used to print to virtually any PostScript device on the network, including printers made by other manufacturers. Instead of downloading individual printer drivers for each product in each office, users can download the single, simple, Mobile Express Driver.
Xerox® Wireless Print Solutions Adapter (Optional)	The Xerox® Wireless Print Solutions Adapter seamlessly connects your Xerox® printer or multifunction printer to modern mobile and desktop workflows, regardless of your office environment. The Xerox® Wireless Print Solutions Adapter is your choice when: • Your printer or multifunction printer is not connected to a network but you want the ability to print from mobile devices. • You need to bridge Wi-Fi connectivity with a traditional hardwire network. • You want Google Cloud Print™ 2.0 (print device requires Adobe® PostScript® compatibility) or Mopria® capabilities. • You want NFC tap-to-pair capabilities (requires the Xerox® Print Service Plug-in for Android). • You own a Xerox® printer or multifunction printer without embedded Apple® AirPrint™ support and want to add AirPrint compatibility (requires PostScript compatibility. The Xerox® Wireless Print Solutions Adapter's AirPrint functionality works with all Xerox® printers and multifunction printers that natively support AirPrint, and enables AirPrint on older Xerox® devices listed below that do not natively support AirPrint.) • You want Wi-Fi Direct, which lets you connect your computer or mobile device to your printer or multifunction printer wirelessly without the need for an access point or existing Wi-Fi network. • You need performance that comes from the cutting-edge Wi-Fi 802.11ac standard, which ensures data transfer that's almost twice as fast as existing 802.11n devices. • You need 256-bit encryption and advanced wireless security protocols, including WPA2™ Enterprise, HTTPS, and industry-standard 802.1X authentication. For more information, visit **www.xerox.com/WPSA**.

Device Specifications

Duty Cycle

	Up to 80,000 pages per month[2]

Recommended Monthly Print Volume

	Up to 5,000 pages per month[3]

Power Consumption	Phaser 6600	WorkCentre 6605
110-127 VAC, 50/60 Hz, 10A		
Printing (average operations)	540 watts	520 watts
Standby Mode	65 watts	69 watts
Power Save Mode	3.3 watts	5.7 watts
220-240 VAC, 50/60 Hz, 5A		
Printing (average operations)	520 watts	560 watts
Standby Mode	64 watts	72 watts
Sleep Mode	4 watts	5.9 watts
Warm up (from sleep)	As fast as 21 seconds	As fast as 25 seconds
Warm up (from power on)	As fast as 40 seconds	As fast as 44 seconds
Storage Temperature Range	32° to 95° F (0° to 35° C)	
Operating Temperature Range	50° to 90° F (10° to 32° C)	
Operating Humidity	10% to 85%	
Storage Humidity	5% to 85%	
Operating Altitude	Up to 3,100 meters	
Shipping Altitude	Up to 15,000 meters when pressurised at 70.9275 KPa or greater	

Xerox® Phaser® 6600 and Xerox® WorkCentre® 6605

Sound Pressure Levels	Phaser 6600		WorkCentre 6605	
Printing / Copying	53 dB(A)		52 dB(A)	
Standby	29 dB(A)		29 dB(A)	
Sound Power Levels				
Printing / Copying	6.9 B		6.8 B	
Standby	4.5 B		4.4 B	
Dimensions and Weights (Unpackaged)	**Width**	**Depth**	**Height**	**Weight** (with CRUs)
Phaser 6600	16.9 in. / 430 mm	19.2 in. / 488 mm	15.1 in. / 384 mm	56.2 lbs / 25.5 kg
WorkCentre 6605	16.9 in. / 430 mm	20.8 in. / 528 mm	22 in. / 560 mm	71.7 lbs / 32.5 kg
550-sheet Feeder	16.8 in. / 427 mm	19.1 in. / 485 mm	5.4 in. / 138 mm	5.7 lbs / 2.6 kg
Stand	17.4 in / 442 mm	18.5 in. / 470 mm	15.4 in. / 390 mm	29 lbs / 13.3 kg
Dimensions and Weights (Packaged)	**Width**	**Depth**	**Height**	**Weight**
Phaser 6600	22.4 in. / 570 mm	27 in. / 686 mm	20.7 in. / 526 mm	67.2 lbs / 30.5 kg
WorkCentre 6605	22.4 in. / 570 mm	27 in. / 686 mm	27.8 in. / 706 mm	82.7 lbs / 37.5 kg
550-sheet Feeder	23.2 in. / 590 mm	21.4 in. / 544 mm	9.5 in. / 241 mm	11.5 lbs / 5.2 kg
Stand	20.3 in / 515 mm	20.1 in. / 510 mm	9.1 in. / 230 mm	33 lbs / 15.4 kg

Certifications

FCC Part 15 Class B, RoHS Directive 2002/95/EC, WEEE Directive 2002/96/EC, Low Voltage Directive 2006/95/EC, EN 60950-1, EN 60825-1 – Class 1 Laser Product, EMC Directive 2004/108/EC, EN 55022, Class B, EN 55024, Listed to UL/CSA 60950-1, FDA 21 CFR Part 1010, 1040 – Class 1 Laser Product, CB Report, IEC 60950-1, IEC 60825-1 – Class 1 Laser Product, Section 508 ADA

ENERGY STAR® (DN configuration), Microsoft WHQL, Adobe® PostScript®, PANTONE®, ECMA 370 Declaration (Nordic), GOST/NOM, GS Mark, Environmental Choice, Xerox® Green World Alliance, USB 2.0 Hi-Speed, WiFi Alliance (option), WLAN certified (option), Apple® Bonjour, IPv6 Ready logo, Citrix Ready, SAP, PTT (WorkCentre 6605 only)

What Comes in the Box

Phaser 6600 or WorkCentre 6605
Starter Toner Cartridges – One of each (Cyan, Magenta, Yellow: 2,000 print capacity[4]; Black: 3,000 print capacity[4])
Quick Use Guide, Quick Install Guide
Software and Documentation CD (with Drivers, User Manual and Warranty Statement)
Scan Software (WorkCentre 6605 only)
Power cord
Fax cord (WorkCentre 6605 only)

Supplies and Options	Description	Order Number
Standard-Capacity Print Cartridges[4]	Black: 3,000 pages	106R02252
	Cyan: 2,000 pages	106R02249
	Magenta: 2,000 pages	106R02250
	Yellow: 2,000 pages	106R02251
High-Capacity Print Cartridges[4]	Black: 8,000 pages	106R02236
	Cyan: 6,000 pages	106R02233
	Magenta: 6,000 pages	106R02234
	Yellow: 6,000 pages	106R02235
Routine Maintenance Items[5]	Imaging Unit Kit: Up to 60,000 pages	108R01121
	Waste Cartridge: Up to 30,000 pages	108R01124
	Fuser Assembly: Up to 100,000 pages	115R00076
	Transfer Unit Kit: Up to 100,000 pages	108R01122
	550-sheet Feeder	097S04400
	Stand	497K13660
	Productivity Kit (512 MB RAM)	097S04269
	Productivity Kit (160 GB Hard Drive)	097S04403
	Wireless Networking Adapter	097S04409

[1] Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
[2] Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
[3] Range reflects the number of pages per month the product can regularly print while maintaining optimal performance (considering factors including supplies replenishment and reliability over the expected product life).
[4] Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.
[5] Average standard pages. Yield will vary depending on job run length, media size and orientation.

xerox ®